

IN THE CLAIMS:

1. (amended) A first-side optical data storage disk comprising:

a ~~circular~~ substrate having first and second principal surfaces;

a first metal/alloy layer overlying said the first principal surface of said the substrate;

a first transparent layer overlying said the first metal/alloy layer, the first transparent layer having a thickness of greater than 15 microns; and

a second metal/alloy layer overlying said the first transparent layer; and

a first optical coupling layer overlying the second metal/alloy layer, wherein the thickness of the first optical coupling layer is substantially less than the thickness of the first transparent layer, the first-side optical disk having an absence of additional layers overlaying the first optical coating such that the first optical coupling layer functions to optically couple the second metal/alloy later to the first-side optical disk's operating environment -wherein each of said metal/alloy layers is adapted to be read by a laser beam that does not pass through said substrate.

2. (original) The first-side optical data storage disk of Claim 1 wherein said first principal surface of said substrate comprises premastered data which includes a series of pits and/or bumps, said first metal/alloy layer conforming to the shape of said pits and/or bumps.

3 (original) The first-side optical data storage disk of Claim 2 wherein the transmissivity of said second metal/alloy layer at the wavelength of said laser beam is greater than 10%.

4. (original) The first-side optical data storage disk of Claim 2 wherein said first metal/alloy layer contains a writeable area.

LAW OFFICES OF
MACPHERSON KWOK CHEN &
HEID LLP
2403 MICHELSON DRIVE
SUITE 210
IRVING CA 92612
(949) 752-7040
FAX (949) 752-7049

- A2
cont.
5. (original) The first-side optical data storage disk of Claim 1 wherein said first metal/alloy layer contains a writeable area.
 6. (original) The first-side optical data storage disk of Claim 5 wherein the transmissivity of said second metal/alloy layer at the wavelength of said laser beam is in the range of 25% to 50%.
 7. (original) The first-side optical data storage disk of Claim 5 wherein said second metal/alloy layer contains a writeable area.
 8. (original) The first-side optical data storage disk of Claim 1 wherein said second metal/alloy layer comprises premastered data which includes a series of pits and/or bumps.
 9. (original) The first-side optical data storage disk of Claim 1 wherein said second metal/alloy layer contains a writeable area.
 10. (original) The first-side optical data storage disk of Claim 1 wherein said first metal/alloy layer comprises aluminum.
 11. (original) The first-side optical data storage disk of Claim 10 wherein said second metal/alloy layer comprises SbInSn.
 12. (amended) The first-side optical data storage disk of Claim 1 comprising:

LAW OFFICES OF
MACPHERSON KWOK CHEN &
REID LLP
2402 MICHELSON DRIVE
SUITE 210
IRVINE CA 92612
(949) 752-7040
FAX (949) 752-7049

a third metal/alloy layer underlying said second principal surface of said single substrate;

a second transparent layer underlying said third metal/alloy layer, the second transparent layer having a thickness of greater than 15 microns; and

a fourth ~~metal/ally~~ metal/alloy layer underlying said second transparent layer; and

a second optical coupling layer overlying the fourth metal/alloy layer, wherein the thickness of the second optical coupling layer is substantially less than the thickness of the second transparent layer, the first-side optical disk having an absence of additional layers underlaying the second optical coating such that the second optical coupling layer functions to optically couple the fourth metal/alloy later to the first-side optical disk's operating environment.

13. (original) The first-side optical data storage disk of Claim 12 wherein said second principal surface of said substrate comprises premastered data which includes a series of pits and/or bumps in said substrate, said third metal/alloy layer conforming to the shape of said pits and/or bumps.

14. (original) The first-side optical data storage disk of Claim 13 wherein said third metal/alloy layer contains a writeable area.

15. (original) The first-side optical data storage disk of Claim 12 wherein said second metal/alloy layer comprises premastered data which includes a series of pits and/or bumps.

16. (original) The first-side optical data storage disk of Claim 15 wherein said second metal/alloy layer contains a writeable area.

LAW OFFICES OF
MACPHERSON KWOK CHEN &
HOTO LLP
2402 MITCHELLSON DRIVE
SUITE 210
IRVINE CA 92612
(949) 752-7040
FAX (949) 752-7049

17. (original) The first-side optical data storage disk of Claim 13 wherein said second metal/alloy layer contains a writeable area.

18. (original) The first-side optical data storage disk of Claim 1 wherein said substrate comprises polycarbonate.

19. (original) The first-side optical data storage disk of Claim 1 wherein said first transparent layer comprises a photopolymer resin.

20. (original) The first-side optical data storage disk of Claim 1 wherein said first transparent layer comprises a curable polymer.

21. (original) The first-side optical data storage disk of Claim 1 wherein said first transparent layer comprises a UV curable material.

22. (original) The first-side optical data storage disk of Claim 1 wherein said substrate has a thickness in the range of 200 to 1000 μm .

23. (original) The first-side optical data storage disk of Claim 22 wherein said substrate has a thickness of approximately 500 μm .

24. (original) The first-side optical data storage disk of Claim 1 wherein said first transparent layer has a thickness in the range of 15 to 200 μm .

A2
cont.

LAW OFFICES OF
MACPHERSON KWOK CHEN &
HEID LLP
2402 MICHELSON DRIVE
SUITE 210
IRVINE CA 92612
(949) 752-7040
FAX (949) 752-7049

25. (original) The first-side optical data storage disk of Claim 24 wherein said first transparent layer has a thickness of approximately 50 μm .

26. (original) The first-side optical data storage disk of Claim 1 comprising a protective coating between said first metal/alloy layer and said first transparent layer.

27. (cancelled)

28. (cancelled)

29. (cancelled)

A2
CONT.
30. (original) The first-side optical data storage disk of Claim 1 wherein the reflectivity of said first and second metal/alloy layers at the wavelength of said laser beam is greater than 25%.

31. (original) The first-side optical data storage disk of Claim 1 wherein said disk is less than 50 mm in diameter.

32. (original) The first-side optical data storage disk of Claim 31 wherein said disk is at or below 32 mm in diameter.

33. (original) The first-side optical data storage disk of Claim 1 wherein said first metal/alloy layer is a read-only layer and said second metal/alloy layer comprises a writeable area, said

LAW OFFICES OF
MACPHERSON KWOK CHEN &
HEID LLP
2402 MICHELSON DRIVE
SUITE 210
IRVINE CA 92612
(949) 732-7040
FAX (949) 732-7049

writeable area comprising a code which permits access to a portion of data recorded on the first metal/alloy layer.

34. (original) The first-side optical data storage disk of Claim 33 wherein said coded permits access to a portion of data recorded on the second metal/alloy layer.

35. (amended) A method of reading data ~~from the first-side optical data storage disk of Claim~~
+ comprising:

providing an first-side optical disk including:

a single substrate having first and second principal surfaces;

a first metal/alloy layer overlying the first principal surface of said substrate;

a first transparent layer overlying the first metal/alloy layer, the first transparent layer having a thickness of greater than 15 microns;

a second metal/alloy layer overlying the first transparent layer; and

a first optical coupling layer overlying the second metal/alloy layer, wherein the thickness of the first optical coupling layer is substantially less than the thickness of the first transparent layer, the first-side optical disk having an absence of additional layers overlying the first optical coating such that the first optical coupling layer functions to optically couple the second metal/alloy later to the first-side optical disk's operating environment;

directing a laser beam from above the principal surface of the substrate towards the first and second metal/alloy layers such that the laser beam is partially reflected from and partially transmitted through the second metal/alloy layer:

detecting a first portion of the laser bean that is reflected from the first metal/alloy layer; and

A2
Cont.

LAW OFFICES OF
MACPHERSON KWOK CHEN &
HEO LLP
2402 MICHELSON DRIVE
SUITE 210
IRVINE CA 92612
(949) 752-7049
FAX (949) 752-7049

detecting a second portion of the laser beam that is reflected from the second metal alloy layer.

Claims 36-57. (cancelled)

A2
cont.

LAW OFFICES OF
MACPHERSON KWOK CHEN &
HEED LLP
2403 MICHELSON DRIVE
SUITE 210
IRVING CA 92612
(949) 752-7040
FAX (949) 752-7049